

**Zydex®**

## **MASONRY / CONCRETE CRACKS / GAPS ?**



JUST  
**Seal-it**





For sealing of Masonry or Concrete Cracks / Gaps and Windowsill.  
Useful for both interior & exterior application.

## FEATURES & BENEFITS

### WATER RESISTANT & UV RESISTANT

Ensures long term protection  
Seals & waterproofs cracks

### DURABLE

Upon application and evaporation, it forms a non-shrinkable, water resistant, flexible seal.

### ADHESION

Extremely strong adhesion on Siliceous surfaces

### FLEXIBLE

Can withstand crack movement of 7-10 %

### VERSATILE

Applicable on concrete, brickwork, ceiling, skirting, wood, aluminum, etc

### WATER BASED

## SPECIFICATIONS

Physical Appearance : White viscous, ready to use paste

Specific Gravity : 1.6 to 1.7

Solid content : 87 ± 1 %

Drying Time : Touch dry : 4-6 hours. Complete drying : 7 days

## APPLICATION METHOD

- 1 Clean the surface thoroughly. Remove dust, loose particles, oil & grease. Allow it to dry completely.
- 2 Using a cutter, open up the cracks / gaps to form a V shaped groove. This will help proper application of **Seal-it** and ensure strong adhesion with the substrate.
- 3 Clean the crack / gap groove thoroughly. Remove all loose particles.
- 4 **For best results** : Flood the cracks / gaps with Zycosil<sup>+</sup> solution (1 part Zycosil<sup>+</sup>, 2 parts Zycoprime<sup>+</sup> and 20 parts water). Let it dry for 6-8 hours. This ensures that the cracks / gaps are now internally waterproofed.
- 5 Apply **Seal-it** with a spatula / hand, and push it hard in the cracks / gaps (*upto 5 mm width*) as deep as possible.

### PRE PAINTING APPLICATION

Allow the **Seal-it** filled cracks / gaps to dry completely. Sand it. Apply primer and paint on it, as per the recommendations of the manufacturer.

### PACKING

600 gms & 1.2 kg.

### STORAGE

Store between +5°C and +45°C.

### SHELF LIFE

1 year if stored as recommended.

### DISCLAIMER

Whilst the information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.



### ZYDEX INDUSTRIES

61, Gotri Sevasi-Road, Vadodara - 390 021, Gujarat, INDIA.

Tel : +91 265 3312000 Toll Free No. : 1800 - 3000 - 7144

E-mail : [waterproof@zydexindustries.com](mailto:waterproof@zydexindustries.com) [www.zydexindustries.com](http://www.zydexindustries.com)